



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## CLC-306SM

### CLC-306SM Induction canopy light Fixture



- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% maintained lumens over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 4700K, 90 CRI
- Voltage: 120V-277V, standard 480V optional
- Applications: Exterior, parking garages, gas stations, freezers
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Die cast housing, clear borosilicate glass drop lens

#### Lamp Specifications

Wattage	Lumens	CRI	PUPIL LUMENS	CCT(KELVIN)	Rated Life
CLC-306SM-120IND	11,400	90	18,810	4700K	100,000 HRS
CLC-306SM-150IND	14,250	90	23,513	4700K	100,000 HRS
CLC-306SM-200IND	19,000	90	31,350	4700K	100,000 HRS

#### Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
126W	120-277VAC	1.05A-0.45A	233KHz	.99	-31°F- 239°F	<10%
156W	120-277VAC	1.30A-0.56A	233KHz	.99	-31°F- 239°F	<10%
210W	120-277VAC	1.75A-0.76A	233KHz	.99	-31°F- 239°F	<10%

#### Ordering Guide

Example: (CLC-306SM-150IND-50-120V-WH-DIM)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
CLC-306SM CANOPY FIXTURE	120W-120IND 150W-150IND 200W-200IND	27-2700K 35-3500K 41-4100K 47-4700K 50-5000K 60-6000K	120-277V 480V	N/A	WH-WHITE BLK-BLACK BZ-BRONZE C-CUSTOM	DIM-DIMMING

