




DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLC-311GL CLC-311GL Parking garage fixture



- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% maintained lumens over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 4700K, 90 CRI
- Voltage: 120-277 standard 480v optional
- Applications: Parking areas, entrances, underpasses
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy duty die cast aluminum body, clear polycarbonate lens



Lamp Specifications

Wattage	Lumens	CRI	PUPIL LUMENS	CCT(KELVIN)	Rated Life
CLC-311GL-40IND	3,800	90	6,270	4700K	100,000 HRS
CLC-311GL-65IND	6,175	90	10,189	4700K	100,000 HRS
CLC-311GL-80IND	7,600	90	12,540	4700K	100,000 HRS
CLC-311GL-120IND	11,400	90	18,810	4700K	100,000 HRS

Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
44W	120-277VAC	0.36-0.16A	233KHz	.99	-31°F- 239°F	<10%
70W	120-277VAC	0.58-0.25A	233KHz	.99	-31°F- 239°F	<10%
84W	120-277VAC	0.70-0.30A	233KHz	.99	-31°F- 239°F	<10%
125W	120-277VAC	1.05-0.45A	233KHz	.99	-31°F- 239°F	<10%

Ordering Guide

Example: (CLC-311GL-80IND-50-120/277V-EZ-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
CLC-311GL GARAGE CANOPY FIXTURE	40W-40IND 65W-65IND 80W-80IND 100W-100IND 120W-120IND	27-2700K 35-3500K 41-4100K 47-4700K 50-5000K 60-6000K	120-277V 480V	CEILING MOUNT EZ-QUICK MOUNT	GRY- GRAY CUS-CUSTOM	PC-PHOTO CELL DIM-DIMMING