



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLW-305WP



CLW-305WP Induction wall pack

- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% maintained lumens over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 4700K, 90 CRI
- Voltage: 120-277 standard
- Applications: Exterior walls, parking areas, entrances, walkways
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy duty die cast back plate, prismatic polycarbonate lens

Lamp Specifications

Wattage	Lumens	CRI	Pupil Lumens	CCT(KELVIN)	Rated Life
CLW-305WP-40IND	3,800	90	6,270	4700K	100,000 HRS
CLW-305WP-65IND	6,175	90	10,189	4700K	100,000 HRS

Ballast Specifications

System Wattage	Input Voltage +/- 30%	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
44W	120-277VAC	0.36-0.16A	233KHz	.99	-31°F- 239°F	<10%
70W	120-277VAC	0.58-0.25A	233KHz	.99	-31°F- 239°F	<10%

Ordering Guide

Example: (CLW-305WP-40IND-47-120/277V-YM-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
CLW-305WP WALL PACK	40W-40IND 65W-65IND	27-2700K 35-3500K 41-4100K 47-4700K 50-5000K 60-6000K	120-277V	Wall Mount	BZ- BRONZE	PC-PHOTO CELL DIM-DIMMING

