



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

LG-CLP-313FL

LG-CLP-313FL Induction Flood light Fixture



- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% maintained lumens over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 4700K, 90 CRI
- Voltage: 120, 208, 240, 277, standard 120-277v , 480v optional
- Applications: Exterior, parking areas, entrances, walkways, underpasses, billboards
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy gauge Aluminum Body, clear tempered glass lens

Lamp Specifications

Wattage	Lumens	CRI	Pupil Lumens	CCT(KELVIN)	Rated Life
LG-CLP-313FL-200IND	19,000	90	31,350	4700K	100,000 HRS
LG-CLP-313FL-250IND	23,750	90	39,188	4700K	100,000 HRS

Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
210W	120-277VAC	1.75-0.76A	233KHz	.99	-31°F- 239°F	<10%
260W	120-277VAC	2.16-0.94A	233KHz	.99	-31°F- 239°F	<10%

Ordering Guide

Example: (LG-CLP-313FL-200IND-47-120V-CFL)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
LG-CLP-313FL Flood Fixture	200W-200IND 250W-250IND	27-2700K 35-3500K 41-4100K 50-5000K	120-277V 480V	SF- SLIP FITTER YM- YOKE MOUNT	BZ-Bronze BLK-Black C-Custom finish	CFL- Clear flat lens FFL-Frosted flat lens

