



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

LG-CLW-307WP

LG-CLW-307WP Induction Wall Pack Fixture



- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 5000K, 90 CRI
- Voltage: 120, 208, 240, 277, 480 standard 120-277v optional
- Applications: Exterior walls, parking areas, entrances, walkways, underpasses
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy duty die cast aluminum body, prismatic borosilicate glass lens

Lamp Specifications

Wattage	Lumens	CRI	CCT(KELVIN)	Rated Life
LG-CLW-307WP-40IND	3,800	90	5000k	100,000 hours
LG-CLW-307WP-65IND	6,175	90	5000k	100,000 hours
LG-CLW-307WP-80IND	7,600	90	5000k	100,000 hours

Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
44W	120-277VAC	0.36-0.15A	233 KHz	0.99	-31°F-239°F	<10 %
70W	120-277VAC	0.58-0.25A	233 KHz	0.99	-31°F-239°F	<10 %
84W	120-277VAC	0.70-0.30A	233 KHz	0.99	-31°F-239°F	<10 %

Ordering Guide

Example: (LG-CLW-307WP-40IND-50-120V-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
LG-CLW-307WP	40W-40IND 65W-65IND 80W-80IND	27-2700K 35-3500K 41-4100K 50-5000K 60-6000K	120V 220V 240V 277V 120-277V	N/A	BZ- BRONZE WHT-WHITE BLK-BLACK SIL-SILVER CUS-CUSTOM	PC-PHOTO CELL GS-GLARE SHIELD BFL-BAFFLE/VISOR WG-WIRE GUARD

