



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

LG-CLW-309WP

LG-CLW-309WP Large Induction Wall Pack



- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 5000K, 90 CRI
- Voltage: 120, 208, 240, 277, 480 standard 120-277v optional
- Applications: Exterior walls, parking areas, entrances, walkways, underpasses
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy duty die cast aluminum body, clear tempered glass



Lamp Specifications

Wattage	Lumens	Pupil Lumens	CRI	CCT(KELVIN)	Rated Life
80W	7,600	12,540	90	5000k	100,000 hours
100W	9,500	15,675	90	5000k	100,000 hours
120W	11,400	18,810	90	5000k	100,000 hours
150W	14,250	23,512	90	5000k	100,000 hours

Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Operating Temp	THD
84W	120-277VAC	0.70-0.30A	233 KHz	0.99	-31°F-239°F	<10 %
105W	120-277VAC	0.88-0.38A	233 KHz	0.99	-31°F-239°F	<10 %
126W	120-277VAC	1.05-0.45A	233 KHz	0.99	-31°F-239°F	<10 %
156W	120-277VAC	1.30-0.56A	233 KHz	0.99	-31°F-239°F	<10 %

Ordering Guide

Example: (LG-CLW-309WP-80IND-50-120V-WM-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
LG-CLW-309WP WALL PACK	80W-80IND 100W-100IND 120W-120IND 150W-150IND	27-2700K 35-3500K 41-4100K 50-5000K 60-6000K	120V 220V 240V 277V 120-277V	WM-WALL MOUNT	BZ- BRONZE WHT-WHITE BLK-BLACK SIL-SILVER CUS-CUSTOM	PC-PHOTO CELL GS-GLARE SHIELD

