



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

SM-CLP-303AL

SM-CLP-303AL Induction Wall pack / Post Fixture



- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% maintained lumens over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 4700K, 90 CRI
- Voltage: 120-277 standard 480v optional
- Applications: Exterior walls, parking areas, entrances, walkways, underpasses
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy duty die cast aluminum body, clear tempered glass lens

Lamp Specifications

Wattage	Lumens	CRI	Pupil Lumens	CCT(KELVIN)	Rated Life
SM-CLP-303AL-40IND	3,800	90	6,270	4700K	100,000 HRS
SM-CLP-303AL-65IND	6,175	90	10,189	4700K	100,000 HRS
SM-CLP-303AL-80IND	7,600	90	12,540	4700K	100,000 HRS
SM-CLP-303AL-100IND	9,500	90	15,675	4700K	100,000 HRS

Ballast Specifications

System Wattage	Input Voltage +/- 30%	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
44W	120-277VAC	0.37-0.16A	233KHz	.99	-31°F- 239°F	<10%
70W	120-277VAC	0.58-0.25A	233KHz	.99	-31°F- 239°F	<10%
84W	120-277VAC	0.70-0.30A	233KHz	.99	-31°F- 239°F	<10%
106W	120-277VAC	0.88-0.38A	233KHz	.99	-31°F- 239°F	<10%

Ordering Guide

Example: (SM-CLP-303AL-80IND-47-120/277V-YM-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
SM-CLP-303AL SMALL ADJUSTABLE AREA LIGHT/ WALL LIGHT	40W-40IND 65W-65IND 80W-80IND 100W-100IND	27-2700K 35-3500K 41-4100K 47-4700K 50-5000K 60-6000K	120-277V 480V	WM -WALL MOUNT PM1- SINGLE HEAD PM2 -DUAL HEAD PM3-TRIPLE HEAD PM4-QUAD HEAD	BZ- BRONZE WHT-WHITE BLK-BLACK SIL-SILVER CUS-CUSTOM	PC-PHOTO CELL WG-WIRE GUARD PLY-POLY CARB LENS GS-GLARE SHIELD BFL-BAFFLE/VISOR DIM-DIMMING

