




DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLW-301FL



CLW-301FL Induction wall pack light Fixture

- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% maintained lumens over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 4700K, 90 CRI
- Voltage: 120v, 277v standard 120-277v optional
- Applications: Exterior walls, parking areas, entrances, walkways, underpasses
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy duty die cast aluminum body, clear tempered glass lens



Lamp Specifications

Wattage	Lumens	CRI	Pupil Lumens	CCT(KELVIN)	Rated Life
CLW-301FL-15IND	1,425	90	2,352	4700K	100,000 HRS
CLW-301FL-23IND	2,185	90	3,606	4700K	100,000 HRS
CLW-301FL-40IND	3,800	90	6,270	4700K	100,000 HRS
CLW-301FL-65IND	6,175	90	10,189	4700K	100,000 HRS

Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
19W	90-150VAC	0.21-0.13A	233KHz	.99	-31°F- 239°F	<10%
25W	120-277VAC	0.21-0.09A	233KHz	.99	-31°F- 239°F	<10%
44W	120-277VAC	0.48-0.29A	233KHz	.99	-31°F- 239°F	<10%
70W	120-277VAC	0.78-0.47A	233KHz	.99	-31°F- 239°F	<10%

Ordering Guide

Example: (CLW-301FL-40IND-50-120V-SF-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
CLW-301FL FLOOD LIGHT	15W-15IND 23W-23IND 40W-40IND 65W-65IND	27-2700K 35-3500K 41-4100K 47-4700k 50-5000K 60-6000K	120V 220V 240V 277V 120-277V 480V	AK -ADJ. KNUCKLE SF- SLIP FITTER PTF- POST TOP FITTER	BZ- BRONZE WHT-WHITE BLK-BLACK SIL-SILVER CUS-CUSTOM	PC-PHOTO CELL WG-WIRE GUARD PLY-POLY CARB LENS GS-GLARE SHIELD